

Mobile Printer Series

SPRT SP-TIII Mobile Printer



General Features

- Pocket size 102 x 77 x 44mm & light-weight (275g complete)
- 58mm paper width
- High Speed Thermal (up to 65mm/sec)
- RS232C, IrDA® & *Bluetooth* wireless interfaces
- Internal rechargeable battery
- Low power consumption
- UK or European charger, carry case & belt clip included
- Easy paper loading by CLAMSHELL design
- Windows™, PDA Programs & Software

Developer's Kit supplied

The SPRT SP-TIII is an alternative, low cost, mobile thermal printer. Its compact dimensions mean it can be carried in a pocket or clipped onto a belt. A carrying case is included.

Interfaces include RS-232C and IrDA or Bluetooth wireless interfaces, ideal for mobile receipting, door to door selling (or collecting) and outdoor events.

With high capacity Li-Ion batteries as standard, the printer can be used for a prolonged period before recharging (which only takes 3 hours). It can be used during the charge cycle and has an impressive standby time of over 15 days!

SPRT

Applications

Mobile POS, Field sales and service, Transportation, Hospitality, Parking, Utility billing, Safety Material management, Law enforcement, testers and timing equipment.

Detailed Specifications

SPECIFICATION	SP-TIII-IR	SP-TIII-BT
Printing	Direct Thermal - CLAMSHELL auto load	
Characters per line	32 & 42	
Character size	12x24 & 24x24 dots	
Resolution	203 dpi, 8 dots/mm	
Print width	2 inch (48mm, 384 dots)	
Printing speed	50mm/sec (avg), 65mm/sec (max)	
Dimensions (WxDxH)	77 x 102 x 44mm	
Weight	275g (inc. battery pack & paper roll)	
Interfaces	IrDA1.1, IrCOMM, RAW-Ir & RS232C	Bluetooth & RS232C
Paper supplied	Thermal roll paper 58mm wide, 40mm diameter 17.5m (approx length)	
Battery	Rechargeable 7.2VDC Li-ion 1.5AH provides 100m continuous printing @ 25% duty cycle, standby time: over 15 days	
Charger	Input: 85~240VAC 50~60Hz, Output:9VDC 3 hours full charge time	
Print head life	50km	
Relative humidity	20 to 85% (non condensing)	
Operating temperature	5~45°C	

Includes...

- SP-TIII - Thermal Paper Roll: Part code MLX058040TPR (additional rolls sold in boxes of 20)
- Serial interface cable approx. length 0.8m, terminates with 9 way D socket - please ask for customised length and termination
- Battery charger (integrated plug, UK type) with 1.5m cord
- Carry case with belt clip
- Belt clip

Accessories

- EU or US style battery charger